

PRODUCT DATA SHEET

REXLTON GXN HIGH QUALITY GEAR PRO SAE 90 / SAE 140 API GL-4

REXLTON™ GXN GEAR PRO series are multifunctional mono-grade gear lubricants which formulated based on high quality base oils fortified with selected “sulfur-phosphorus” additive system to provide excellent gear protection to those equipment and vehicles working in medium severity conditions. The products are recommended for use in manual gearboxes of passenger cars and commercial vehicles requiring API GL-4 performance.

PERFORMANCE LEVEL

API GL-4

TYPICAL PROPERTIES:

PROPERTIES	METHOD	VALUE	VALUE
SAE Viscosity Grade	-	90	140
Appearance	VISUAL	BRIGHT & CLEAR	BRIGHT & CLEAR
Density @ 15°C, g/cm ³	ASTM D4052	0.8833	0.9013
Kinematic Viscosity @ 40°C, cSt	ASTM D7042	166.90	375.40
Kinematic Viscosity @ 100°C, cSt	ASTM D7042	16.09	26.72
Viscosity Index	ASTM D2270	99	96
Flash Point (COC), °C	ASTM D92	220 min	230 min

PERFORMANCE FEATURES:

FEATURES	BENEFITS
High EP performance	Provides excellent load carrying capability.
Excellent thermal & oxidation stability	Reduces oil degradation during high speed/ low torque and low speed/ high torque operating conditions.
Good anti-wear properties	Increases transmission life.
Good rust & corrosion protection	Compatible with sensitive copper alloy components.

PRODUCT DATA SHEET

NOTE:

This specification and data sheet are provided for informational purposes only. Actual product specifications may vary. Always refer to the manufacturer's documentation for specific details and recommendations.

STORAGE & HANDLING:

- Store in a cool, dry, and sheltered place away from direct sunlight.
- Keep containers tightly closed when not in use.
- Follow local regulations for disposal of used oil and containers.

Safety data sheet is available on request.

For more information, please visit www.hextaroiltech.my or email to: info.rexlton@hextar.com