



eni Rotra Gear Tec (Monograde)

eni Rotra Gear Tec is a gear oil series with EP characteristics, recommended for hypoid gears operating under normal conditions. It can also be used in conventional gear-boxes and steering-boxes on cars and trucks, and in gear-boxes, final drives and power take-offs on farm and earth-moving machinery. It can thus be used for lubricating all gears, whatever they are made of, for which the manufacturer recommend an EP lubricant where API GL-5 level is not required.

CHARACTERISTICS (typical figures)

SAE Grade		90	140
Viscosity at 100°C	mm ² /s	14.7	28.3
Viscosity at 40°C	mm ² /s	146	383
Viscosity Index	-	100	101
Flash Point COC	°C	248	250
Pour Point	°C	-21	-21
Mass Density at 15°C	kg/l	0.892	0.898

PROPERTIES AND PERFORMANCE

- Its superior EP additives ensure a continuous lubricant film even on gears operating under the severest conditions involving heavy dynamic and shock loads, and very high, or intermittent sliding speeds between the teeth.
- Its outstanding antiwear properties and its oiliness, markedly reduce gear-tooth and bearing wear. Its particularly good oxidation stability prevents any deterioration even when in contact with components operating at high temperatures. Thus any tendency for viscosity to increase or for sludge to form is inhibited.
- **eni Rotra Gear Tec** can therefore be kept in use for the long oil-service periods specified by car manufacturers.
- **eni Rotra Gear Tec** is noncorrosive to steel, copper and other metals and alloys, and thus helps keep lubricated parts in first-class condition.
- Its antirust properties effectively prevent rust on gears and in bearings even when moisture is present.
- Its antifoam qualities minimize the formation of air bubbles which could adversely affect lubricant film continuity.

SPECIFICATIONS

eni Rotra Gear Tec is officially approved by or meets the requirements of the following service and specifications:

- **API** GL-4